FUNcube-1 Dashboard

Installation and operating guidance notes



Release 1.6 – July 29th 2014

Overview

The FUNcube-1 Dashboard user interface enables the display of telemetry, debug data and Fitter messages from the FUNcube-1 (FC1) spacecraft. It can also upload the received data to the FUNcube Data Warehouse over the internet.

The Dashboard can accept live inputs from a directly connected FUNcube Dongle (both Pro and Pro+ models) or by audio from another SSB radio fed into the computer soundcard. It can also display previously recorded data from IQ "WAV" files or from the ".funcubebin" recordings that it can create during operation.

A different version of this Dashboard is being developed to provide very similar functionality for the FUNcube-2 (FC2) sub-system on the UKube-1 spacecraft which launched on July 8, 2014.

The Dashboard has been tested on a variety of different "Windows" machines, from XP through to W8. It is not yet available for other operating systems (see the FAQs at the end)

This version, v848, of the software is being made available post launch to provide fixes for several issues reported to the FUNcube Project Team. It also includes some additional developments/enhancements that make the use of the Dashboard a little more clearer for users of the FUNcube Dongle (Pro or Pro+ version).. We have also made available links to four IQ wav files produced using SDR#, and a .funcubebin file. All of these sources can be used to populate the Dashboard display. All of the recordings are from the Engineering Model. Not all the sensor channels were implemented on the EM so don't be surprised by some odd data values. They are all present and correct on the Flight Model!

The FUNcube concept is that the spacecraft should operate in educational mode (high power telemetry downlink only) when in sunlight and amateur mode (low power telemetry and transponder) when in eclipse. It is intended that the available data from all of the 50+ telemetry channels can be used by schools and colleges to demonstrate a wide variety of science in an interesting and challenging manner.

Finally – a respectful request – please read ALL of these notes before diving in and trying to install, configure and use the Dashboard. Please note that the authors have assumed that early users will already have experience of using a FUNcube Dongle or of using an SSB VHF receiver!

Pre-Requisites

Prior to updating your station with the capability to receive the FUNcube telemetry, please take a moment to ensure that you register at the FUNcube Data Warehouse at http://warehouse.funcube.org.uk

When you have completed registration, you will be emailed with your login details which consists of

- "Site Id" which is typically your callsign,
- "Auth Code" which is a unique code used to secure your uploaded data to the warehouse, and
- "URL" which is <u>http://data.funcube.org.uk</u>

Please save this data for entry into the Dashboard software.

The Dashboard software requires the Microsoft .NET Framework v4.0 to be installed on your computer. Please download this from http://www.microsoft.com/engb/download/details.aspx?id=17851 and ensure that Windows Update confirms that you have the latest updates installed for it.

We also have a support forum at <u>http://forum.funcube.org.uk</u> for details and support type questions. Again, we encourage you to join the forum and to share your experiences of the Dashboard.

Software Installation

You can download the dashboard from <u>http://funcube.org.uk/working-</u> <u>documents/funcubetelemetry-dashboard/</u> as a Windows Installer (.msi) file. Once you have downloaded the installer, please ensure that you right-click on the MSI file and select "Properties". Ensure that you click on the "Unblock" button if it is displayed.

The dashboard will install directly to your hard disk and you have the option as to which directory the dashboard is placed during the installation. By default, a directory including the release version number will be used (e.g. c:\Program Files\FUNcube\Dashboard-1.0.847.1) to avoid any potential for conflicts with a previously installed version. Beginning with release v806, the settings entered in the "Warehouse" data will be retained when future upgrades to the Dashboard occur. The Dashboard will confirm that it has correctly copied the settings from a previous version (providing it was greater than v806) on the first execution of the Dashboard itself.

To test your station setup, there are seven sample files that can be downloaded and played through the Dashboard. The seven files (one funcubebin recording, two MP3 files and four WAV files) can be downloaded from http://funcube.org.uk/working-documents/telemetry-examples/. Note that the WAV files total about 400MB in size.

Navigating the Dashboard

To start the dashboard, double click on the "dashboard.exe" programme or select "FUNcube Dashboard" from the "Start" menu.

The first screen you will see is shown in Figure 1. There are eleven separate sets of telemetry data displayed on the initial Dashboard screen along with a summary set ("Telemetry Decoding") which gives details on how successful the data decoding is progressing. The last field to appear is usually the "Power Tracking Mode" field at the bottom of the EPS frame on the right hand side or may be the Telemetry Decoding details. This will depend upon your screen resolution etc. Please ensure you resize the Dashboard so that all the data is visible on your screen.



Figure 1 - The FUNcube Dashboard

The initial display shown in Figure 1 is the "RealTime" data. Each box of data represents different segments of the telemetry. Do not be concerned by the erroneous numbers that initially appear in some fields before any real data has been received.

The Dashboard is comprised of four main "Panels" which can be sized to suit the user. The four panels are:-

- 1. The WOD (Whole Orbit Data)/HR (High Resolution) Data Panel.
- 2. The Graphing Panel, and
- 3. The Debug/Tuning Panel
- 4. The Status Bar

The WOD/HR Data panel is in the upper left of the Dashboard. This panel is made up of two views which are selectable via the "Whole Orbit" and "High Resolution" tabs. This panel shows the

different frames of data and clicking on any of the items displays that data in graph form in the Graphing Panel.

The Graphing Panel is the large panel in the upper half of the Dashboard. The contents of this panel can change depending upon the data you are viewing. The display in Figure 1 shows all the data available from the telemetry but graphs and lists of Fitter messages can also be displayed in this panel. Figure 2 shows an example of a graph being displayed in this panel.

The Debug/Tuning panel is the large panel occupying the lower portion of the Dashboard. The Debug tab was primarily for the use of the developers during the development of the telemetry system and allows for the display of the data in hex form as well as internal data from within the Dashboard. When a FUNcube Dongle (Pro or Pro+) is connected to the computer running the Dashboard, the "Tuning" part of this panel will show a spectrum of approximately 96kHz – that is \pm 48kHz centred on the Dongle frequency. The "AutoTune" toggle enables the system to track Doppler shift, or not, as desired by the user.

When data is being captured via the soundcard or being replayed via a file, the Tuning panel will display a spectrum of the received signal. The width of the spectrum in this case is 48kHz.

All of these panels can be resized by placing the mouse pointer over the borders until the mouse pointer changes. Once the Dashboard is arranged to suit your PC display, the configuration can be saved by selecting the "Window" menu option, followed by "Save Layout". The layout can be reloaded by using the "Load Layout" menu option.

The Status Bar is at the very bottom of the Dashboard window. It holds status information for the current Dashboard session.

Detailed descriptions of the Dashboard follow with all the functionality in menus, panels and the status bar described.

Dashboard Menus

"File" Menu

The file menu contains four options.

- "Open Session" option enables you to reload the data contained in a specific ".funcubebin" file. This data will display on the screen exactly as a live session except it can run a little faster.
- "Capture Session" option enables you to record the data already stored in memory from the current session to the hard disk. Files will be saved in the ".funcubebin" format.
- The "Settings" option allows for the configuration of the Dashboard. Please see the "Configuring the Dashboard" section later in this document for details.
- "Exit". Terminates the program. Note that this will terminate the Dashboard completely and all data in memory will be lost if it has not already been saved.

"Capture" Menu

The "Capture" menu has five options. The main purpose of this menu is to select the input that will provide the audio to be decoded by the Dashboard.

- "Capture from Soundcard" This option will take the input from the soundcard that has been selected in the "Settings" panel.
- "Capture from FUNcube Dongle" This option will take the input from a FUNcube Dongle (Pro or Pro+) that is connected to your computer and has been selected as the input on the "Settings" panel. Once selected, the "Tuning" display will start showing a spectrum display of the dongle passband. . If no FUNcube Dongle is detected, this menu will be greyed out and not selectable.

Note that if no FUNcube Dongle is detected, this option cannot be selected. You can attach a FUNcube Dongle whilst the Dashboard software is running and it will be detected. In this case, please return to the "Settings" panel and update the "Input Device" if you wish to capture data from the Dongle.

- "Capture from file" This option will take the input from a file that is selected and load the data in a simulated satellite pass. The time delay between the samples can be varied by the time delay option configured in the "Settings", "Files" option.. [TO BE IMPLEMENTED]
- "Write Capture data to file" This option will allow the saving of the currently captured data to a ".funcubebin" file. This file can then be replayed later, when required, using the "Capture from file" option.

• "Clear" – This option erases the current captured data from memory.

"Window" Menu

The "Window" menu has five options.

- "Load layout" The Dashboard will start every time in a default layout. This option allows the user to load a Dashboard layout that has previously been saved using the "Save layout" option. [TO BE IMPLEMENTED]
- "Save layout" This option saves the current layout of the Dashboard, including the theme, position of the main panels and colour scheme. [TO BE IMPLEMENTED]
- "Themes" This option allows you to select different themes for the Dashboard. There are a number of alternatives offered as well as an option to revert to the default theme ("Expression Dark") which is used every time the Dashboard is started. Note that different themes can, and will, change the location of the tabs on the different panels.
- "Colours" This option allows you to select from a number of alternative colour options for the Dashboard.
- "Show raw data" Under normal operation, the raw telemetry numbers are converted to show actual values with units of measure. Selecting this option allows for the raw decoded data to be displayed without any additional calculations being carried out.

"Help" Menu

This menu has only one option which displays details of the Dashboard software, including version number and release date. There is also a link to the FUNcube website (click on the "More Info" link at the bottom left of the Help box).

A future version of the Dashboard will implement a "Check for Update" feature.

Dashboard Panels

WOD/HR Panel : Whole Orbit tab

WOD contains specific channels of data, sampled on the spacecraft at one min intervals. These telemetry channels can be displayed in graphical form by selecting one of the entries in the list. In flight, the spacecraft will store 104 minutes of data. Figure 2 shows an example of some WOD displayed as a graph.

IMPORTANT Currently the horizontal time scale is that when the data is displayed by the dashboard not when it was actually recorded by the spacecraft. As WOD is only sent in specific frames, this can give a distorted view. If you are playing back a recorded .funcubebin file the displayed time will be the current time.



Figure 2 - Dashboard displaying graphical data

WOD/HR Panel : High Resolution tab

These data channels are read every 5 seconds for a minute every alternate minute. Again these can be displayed in graphical form. One purpose of having this High Resolution data is to facilitate the calculation of the spin rate of the spacecraft.

Graphical Panel : Fitter Messages tab

A Fitter message is a 200 character text message that can be transmitted from the FUNcube satellite as part of the telemetry. There are a total of nine slots transmitted by the spacecraft and new text can be uploaded by Ground Command Stations. It is envisaged that schools wishing to take part in

the science experiments will design a message for them to receive as part of their experiments with FUNcube. Details of how to submit Fitter message for uploading by Command Stations will be released in due course.

There are some preloaded Fitter messages stored on the spacecraft before launch. Fitter message 9 can be switched by Ground Command station from normal text to debug data and we anticipate it will spend most of its time in debug mode.

Graphical Panel : Real Time Data tab

This display shows all the telemetry data on one screen with each type of data contained in separate blocks. These channels are read every 5 seconds and display live or, by clicking on the particular title header, a graph is displayed.

Each time you select a particular telemetry channel to plot, the Dashboard will open a new tab in the Graphical Panel to display the graph. Please note, that in its current form, the dashboard can appear to freeze, or slow down dramatically, if more than a few graphs are displayed.

Debug/Tuning Panel : Debug tab

This display allows for the raw hex telemetry to be displayed. Whilst viewing the hex frames, it is possible to copy the last frame, the last 24 frames or all the decoded frames to the clipboard. The data is copied as plain text.

The debug panel also provides some other displays of data variables that show the settings of some of the adjustable parameters that exist within the on board flight software. More information about these will be made available later

Debug/Tuning Panel : Tuning tab

This is the largest panel at the bottom of the Dashboard and provides a view of the passband when the FUNcube Dongle is the primary input source. Beginning with version v814, the scale on the Tuning Panel is in Hz, centred on the frequency specified in the Settings panel, and is updated with the current FUNcube Dongle frequency if another application is being used to control the Dongle itself. There are several functions available via the right-click option on a mouse and the display can be manipulated/moved around to best suit the requirements of the user. There is also a "Screenshot" option that allows this display to be copied to the clipboard or a file.

To the right of the tuning display, there are a couple of options available to the user. The "Auto Tune" option is available when the input is selected to the FUNcube Dongle. This will allow the Dashboard to track Doppler Shift within the low/high range specified in the "Low" and "High" input fields. The "Monitor Audio" allows for the received audio to be played through the default speakers on the PC.

Dashboard Status Bar

The Dashboard Status Bar provides a wealth of information for the user in terms of the telemetry being received and decoded. Status information is provided as follows:-

The left hand side of Dashboard has four status fields.

- Spacecraft Name This shows from which spacecraft you are receiving data. The options comprise the FUNcube-1 Prototype, Engineering Model (EM), Flight Model (FM) as well as the FUNcube-2 Engineering Model (EM) and Flight Model (FM) and is updated automatically depending upon the source of the signals.
- Frame ID This lists the id of the frame being decoded and what its contents are. More
 information on the format of the data can be found in the Data Downlink specification
 located in the Downloads section of the FUNcube web site (<u>http://funcube.org.uk</u>).
- Sequence ID Each frame of data transmitted by the spacecraft is tagged with a unique ID. This is the Sequence Number. This counts up by one every time a complete sequence of 24 frames has been transmitted. The last Sequence Number recorded from the Flight Model before it was integrated into the ISIPOD was 420. Hopefully we might have some lucky listener in the Southern Hemisphere who is able to catch some frames with a sequence number of 421! There will be a special award for any ground station that is able to upload a frame of data to the FUNcube Warehouse with the sequence ID of 421.
- Received Command This field lists the type of the most recent command received by the spacecraft from the ground as well as showing a Success/Fail status flag for that command.

The right hand side of Dashboard has five status fields.

- FUNcube Dongle If a FUNcube Dongle has been detected as the program starts, it will
 record in this field that a dongle has been found. If no FUNcube Dongle is present, this field
 will be empty.
- Capture Status This indicates the status of the telemetry decode functions. It is either "Capturing" or "Idle".
- Packets Decoded/Missed This field records the number of packets that have been decoded in the current session as well as the number that have been missed.
- Packets Uploaded/Waiting this field records the number of decoded packets that have been uploaded to the Warehouse and the number waiting to be uploaded along with a status of the upload operation to the Warehouse. Note that if the "Settings" option to "Stream Data to Warehouse" is not selected, this field will report "Disabled".
- Detected Frequency This field reports the frequency within the passband where signals are being decoded.

It is possible to reset the decoded and missed message counters by right clicking on the Status Bar and selecting the appropriate option.

Configuring the Dashboard

To configure the Dashboard for use, there are a number of settings that have to be made.

These are:-

- 1. The Audio Configuration
- 2. The Warehouse Connection
- 3. Optional Files.

These settings are access via the "File" menu and the "Settings" option. Upon selection, a new window opens with three tabs labelled "Audio", "Warehouse" and "Files".

Audio Configuration

The FUNcube Dashboard is currently written to decode audio supplied from the FUNcube Dongle (both the Pro and Pro+ versions), a Soundcard device or a pre-recorded file.

"Input Device" – This option lists all the audio devices (soundcards, virtual devices and FUNcube Dongles) that are presently connected to your computer. Select a device as the source for the audio input. Note that if you intend to "Capture from Soundcard", you should select a real soundcard or virtual audio device here. If you intend to "Capture from FUNcube Dongle", please ensure that you select the FUNcube dongle you intend to use – the Dashboard supports multiple FUNcube Dongles connected simultaneously and multiple instances of the Dashboard can be run at the same time. Note that in this case, the Dashboard will only save the settings for one instance of the Dashboard – i.e. it is not possible to store multiple, different, settings for the Dashboard.

"Output Device" – The Dashboard is able to output the audio that it has decoded and send it to a specific audio output device. This option allows you to select a device other than the default output device for your computer.

"Frequency Pre-set" - This is an easy method to select the different satellites that the Dashboard has been designed to work with and to automatically populate the "FCD Frequency" field. The Dashboard currently works for FUNcube-1 and FUNcube-2, both Engineering and Flight Models (EM & FM).

"FCD Frequency" – This field is automatically populated when the "Frequency Preset" dropdown is used or it can be manually populated. The value selected/entered in this field is used to set the centre frequency of the FUNcube Dongle when it is started. When the Dashboard is set in its normal operating mode (i.e. decoding packets), you will then see the spectrum from the Dongle displayed at the bottom of the screen in the Tuning Panel. Note that you may need to adjust your computer sound card settings so that a little "noise" is visible at the bottom of the display in the absence of any actual incoming signal. "FCD Enable Bias T" – This checkbox enables (when ticked) the Bias T function that is available on late versions of the FUNcube Dongle Pro and on all versions of the FUNcube Dongle Pro+. Bias T places a voltage on the antenna and can be used to power remote antenna pre-amplifiers. Please consult the FUNcube Dongle website for details of the maximum current that can be provided to any pre-amplifier.

Once you have made changes to the Audio settings, press the "Save" button to make the changes permanent within the Dashboard.

Warehouse Configuration

This tab enables the user to set up their personal login to the FUNcube Warehouse and to control the streaming of decoded data to the Warehouse.

The information needed for this part of the configuration is as supplied in the email sent after your registration was completed – it is the information as listed in the "Pre-Requisites" section of this document.

Beginning with Dashboard release v806, these settings will be retained when future updates to the Dashboard are released.

Files Configuration

This tab enables you to select whether or not to produce log files (with a .log extension) and where these should be placed. These files contain the data in CSV format and are suitable for use by schools for research and investigations. The last tab on this screen relates to the playback speed for the .funcubebin files which were created using the "Capture from File" menu option. It is possible to adjust the precise speed of playback with this tab. To obtain a realistic speed, i.e. as it was originally transmitted by the spacecraft, set the slider to the slowest setting, this will "playback" at one frame every 5 seconds.

Normal Operation of the FUNcube Dashboard

The FUNcube Dashboard is designed to require very little interaction to receive, record and decode the telemetry from the FUNcube Satellites.

The key steps to making the Dashboard operate and decode data are:-

- 1. Ensure that the Audio Configuration is setup as described in this document.
- 2. If you have registered at the FUNcube Warehouse, select the "Stream to Warehouse" option in the Warehouse settings according to whether you wish to submit data to the Warehouse.
- 3. From the "Capture" menu, select the "Write capture data to disk" (so you can save the data for replay at a later date).
- 4. From the "Capture" menu, select the source for your audio.
- 5. Sit back and enjoy!

Testing your Dashboard Installation

An important step to ensuring your station is ready to receive the FUNcube telemetry, is to test the installation with some sample files or with a FUNcube Dongle.

Testing with a FUNcube Dongle

To use the FUNcube Dongle with the Dashboard, there are a few configuration steps that you need to complete to confirm correct operation. These steps differ according to Dongle version and Operating System.

FUNcube Dongle Pro and Windows XP

Using this combination, simply accept the default settings assigned to the Dongle when you connect it to the computer,

FUNcube Dongle Pro and Windows Vista/7/8

When a Dongle is first connected to a computer, the FUNcube Dongle Pro is configured as a microphone device by the operating system. It is necessary to alter the default "Recording Level" for the Dongle by opening the "Sound" control panel, selecting the "Recording" tab, double clicking on the Dongle device, selecting the "Level" tab and altering the volume slider so that it reads "1".

FUNcube Dongle Pro+ and Windows XP

Using this combination, simply accept the default settings assigned to the Dongle when you connect it to the computer,

FUNcube Dongle Pro+ and Windows Vista/7/8

When the Pro+ Dongle is first connected to a computer, the FUNcube Dongle Pro is configured as a Line-In device by the operating system. It is not necessary to alter any of the default settings that the operating system assigned to the Pro+ Dongle audio device.

With the FUNcube Dongle plugged into the computer and with no antenna connected to the Dongle, start the Dashboard. Ensure that the audio settings for the Dashboard are configured so that the "Input Device" on the "Settings" page is selected to the Dongle. On the "Capture" menu, select on the "Capture from FUNcube Dongle". The Dashboard should look like Figure 3.



Figure 3 - Dashboard running with "Capture from FUNcube Dongle"

Note how the Tuning window now contains a spectrum display that SDR users will be familiar with. This indicates that the Dashboard is successfully receiving audio from the Dongle and processing it to produce the spectrum display. If you have a display like this, your Dongle is working correctly and you are ready to receive real telemetry from the satellite.

Testing with pre-recorded WAV Files.

To test the Dashboard with WAV file, it is necessary to play the .WAV file through a separate piece of software and to direct the output of that software to an audio loopback/virtual audio cable type connection that can be used in the Dashboard.

We recommend testing with SDR# (<u>http://sdrsharp.com</u>) and the following shows how to configure SDR# for use with the Dashboard. It is however possible to use other software that can play .WAV files such as Audacity etc.

With SDR# installed, start the program. A window similar to Figure 4 should appear.



To select a WAV file, use the dropdown box at the top of the SDR# window ("Other (Sound card)") and change the option to " IQ File (*.wav)". This will open a file dialog box for you to select a .WAV files – we suggest using one of the files sample telemetry files from the FUNcube website.

The software should be set to USB and both the "Set IQ" and "Swop IQ" tabs should be ticked.

The only other option to change is the audio output. If you have an audio loopback device, select this, otherwise use a software audio loopback device such as Virtual Audio Cable.

Then click on the "PLAY" button.

Figure 4 - SDR# Initial Screen

SDR# will start playing the file and the spectrum and waterfall will start to fill – see Figure 5 as an example.



Figure 5 - SDR# replaying a .WAV file

Start the Dashboard and on the, "File", "Settings" menu, select the "Input Device" to be the audio loopback device/Virtual Audio Cable and select "Save". Finally, on the "Capture" menu item, select the "Capture from soundcard" option. The Dashboard will look similar to Figure 6.

FUNcube-1 Dashboard									her.	
e Capture Window Help	· Either Marramer Paulti			_		_	_	_	_	
4 Sub Renot Bank X- Bank Y- Pank Y- Pank Y- Took Paul Current Extery Votage	Data Collection Artema Sun LANS Failed Artema Buz LANS Failed Been Sunk (RS) Failed Talled Meteria Sca (MS) Failed Meteria Sca (MS) Failed Meteria Sca (MS) Failed Interface Bear(ISS) Failed	Antenna (AntS) Temperature A 255.0 °C Temperature B 255.0 °C Antenna Listha Undeployed Antenna Listha Undeployed Antenna Status Undeployed Satellite Mode In Ecliste O Antenna Status Undeployed Satellite Mode In Ecliste O Antenna Status Undeployed Satellite Mode In Ecliste O Satellite Mode Satellite Mode Sat	Radio Board (RF) CMD 82 Accessor O Hote CMD 824 SS30 O alter CMD 824 SS30 O alter Terms D mA D mA D mA D mA Power Amplifier (PA) Ennest Damer O mA Power Amplifier (PA) Ennest Damer O MOM mit BBA °C Damer BBA °C Damer D mA	X Panels Valtage 0 mV - Sun Senar 0 mV - Sun Senar 159,24 °C V Panels V Panels	Z Panels Voltage 0 mV - Sun Senser - Sun Senser - Sun Senser - Terme N/A 'C - Terme N/A 'C	Power (ASIB) 3/b-Current 0.00 ma 3/b:Visitage 0.00 mV 3/b:Visitage 0.00 mV	Power (EPS) Bis Connet O mA Bear Connet O mA Bear Connet D mA Bear Connet D ma Connet D ma Connet Connet D ma Connet D ma Connet D ma Connet D ma Connet Connet Co	Telemetry D Encoder 0 Decoder fraguen 0	ecoding g	
Auto Tune 300 I Monitor Audio 200 uto Tune Range: 200 Low: 0 High: 96000				f www.	m					
5	5000 10000	15000 20000 25000	30000 35000 40	000 45000	50000 55	60000	65000 70000	75000 80000	85000 90000	95

Figure 6 - Dashboard displaying signal from a .WAV file

You should also be able to hear the audio on your system speaker – to verify that, untick the "Monitor Audio" check box and the audio should stop. If it doesn't, or there is no display in the Tuning panel, it would suggest that the loopback device/Virtual Audio Cable is not properly configured on your PC. Please stop the Dashboard, check the settings in the Windows Sound control panel and restart the Dashboard.

To get the Dashboard decoding the telemetry from the sample WAV file, it is necessary to set the SDR# filter to cover the signal in the passband. Figure 7 shows the SDR# filter set to cover the signal seen on the spectrum and waterfall displays.



Figure 7 - SDR# filter set to cover telemetry signal

Once the filter is in the correct location, the telemetry signals will be heard from the Dashboard and the Tuning panel will look similar to Figure 8.



Figure 8 - Dashboard showing telemetry signal

The Green/Yellow bar in the middle of the Tuning Display will, in all probability, be moving very quickly. This is because the "Auto-Tuning" function is trying to find the correct signal – remember, the "Auto-Tune" is also trying to account for the Doppler effect on a received signal. You can deselect the "Auto Tune" feature by unticking the check box. Doing so causes the Green/Yellow vertical bar in the Tuning panel to change to a Green/Red vertical bar as shown in Figure 8.



Figure 9 - Manual Tuning in the Tuning Panel

At the base of the Green/Red vertical marker, there is a small circle with a dot at its centre. Placing your mouse on this circle and left-clicking allows you to drag the Green/Red bar over the portion of the signal that you want the demodulator to process.

Note that the Red (or Yellow if "Auto Tune is active) line marks the centre of the demodulator whilst the Green bar indicates the bandwidth of the demodulator itself.

It is also possible to reduce the frequency range within which the "Auto Tune" will function buy setting the "Low" and "High" tuning range. This can be done manually or graphically.

To set the range manually, simply enter the lower and upper frequency ranges and the Tuning panel will look like Figure 10. The white area between the two red boundaries now indicates the frequency range over which the "Auto Tune" function will function.

To set the limits graphically, place the mouse in the Tuning panel and, with the left mouse button held down, move the mouse slightly to the right. This will expose a vertical line at the extreme left of the signal. Where the signal intercepts with this vertical line, there is a small circle. Clicking on this circle and moving it to the right increases the lower frequency value for the "Auto Tune" range. A similar process on the extreme right hand side of the Tuning panel allows for the upper frequency value to be set graphically – see figure 10.

Starting with Dashboard version v847, if the Dashboard is closed whilst "AutoTune" limits have been in use, upon restarting the Dashboard, the last settings of the limits will be restored.



Figure 10 - Tuning Panel showing a restricted Auto Tune Range

The FUNcube Data Warehouse

The Data Warehouse enables listeners to upload the data they receive it to a central data warehouse. It also enables those without their own receivers to track what is happening, live, on the spacecraft. We are hoping that everyone will register at http://warehouse.funcube.org.uk so that the maximum amount of data can be collected from the spacecraft.

Although we have a few "Whole Orbit Data" channels, it will be very useful, to help the Command Team safely manage the spacecraft, if we receive data from all over the world.

The Data Warehouse will also make it possible for any user to download historical datasets in .csv format for educational research. Details of when this functionality is available will be posted on the FUNcube forum.

FAQs

Can I roll my own software?

Yes- The FC1 Downlink Specification document and the FC1 telemetry equations spreadsheet are available here http://funcube.org.uk/working-documents/. We are very keen to receive and retain as much telemetry information as possible so please ensure that you do incorporate this linking to our FUNcube Data Warehouse in any software that you create. For further information on this please contact G4DPZ "dave at g4dpz.me.uk". We have plans to make a DLL available which will facilitate the production of a different 'front end'. The DLL will contain the decoding algorithms.

Is this software "open-source"?

Yes. It is released under a creative commons share alike non-commercial licence, please see: <u>http://creativecommons.org/licenses/by-nc-sa/3.0/</u>

The source code will be available shortly on github..watch this space!

To where do I send comments about this software?

Bugs in this software can be reported via the open forum at <u>http://forum.funcube.org.uk</u>

Please use the query facility to ensure your bug hasn't already been raised, and please try to provide a detailed description and steps to reproduce the fault.

There are also three Yahoo groups which, although they have, up to now, mainly concentrated on the FUNcube Dongle, will provide new users with valuable advice:

<u>http://uk.groups.yahoo.com/group/funcube/</u> This contains a number of user guides and troubleshooting guides in the Files section which are recommended reading. We also strongly recommend searching the mailing list as it's very likely someone has solved a similar issue before.

http://uk.groups.yahoo.com/group/FCDevelopment/ http://www.funcubedongle.com/

Who do I contact if this software does not load or work properly?

See above comments!

If I see telemetry data that indicates a problem on the spacecraft, who should I contact?

Email: <u>operations@funcube.org.uk</u>, this will alert the global monitoring and operations team (who should already know!)

Does this software work on Linux and Mac OS systems?

Not yet, however there are a number of projects in progress to provide decoders for these platforms.

The FCDevelopment Yahoo group is a good starting place to find them or announce your own work: <u>http://uk.groups.yahoo.com/group/FCDevelopment</u>

Is there an iPad or Android app that does the same job?

As above - not yet, but do keep an eye on the FCDevelopment Yahoo group or pitch in and write one yourself!

Will this software work directly with any other type of SDR Dongle?

Not directly, however we would welcome developers who wish to add support for new hardware. Please join the FCDevelopment Yahoo group.

It is of course possible to use other types of SDRs with the usual types of software such as SDR# or SDR-Radio and to use an internal audio loopback device or a software audio device such as Virtual Audio Cable etc.

The example telemetry files are in WAV format – How do I use these?

The Dashboard can read and write files in the .funcubebin file format. To make use of the WAV example files, you need to play the WAV files through an audio player (such as MediaPlayer, Audacity, VLC etc) and then select the input from the soundcard within the Dashboard software.

I have multiple FUNcube Dongles connected – How do I identify them in the Dashboard?

This can be difficult to achieve as the serial number of the Dongle is not used when internally, Windows creates configurations for each USB port that a Dongle is connected to. The best advice we can offer is to start with just one dongle plugged into a specific USB port and note that configuration. Check it functions with the Dashboard before adding a subsequent dongle.

I can't get the Dashboard to work with my FUNcube Dongle or particular soundcard?

Please double check the settings you have selected in the "Settings" panel for "Input Device" and the device you have selected in the "Capture" menu – they MUST be of the same type. That is, if the "Input Device" is set to a FUNcube Dongle, then the "Capture" must be set to the FUNcube Dongle. Setting the "Input Device" to be a FUNcube Dongle but setting the "Capture" to be from a soundcard will give a display in the Tuning panel but it will not be what you are expecting!

On the "Telemetry Decoding" data shown on the "Real Time" display, what does "Error Count" mean?

Each frame of data transmitted from the spacecraft is 5200 bits with the telemetry data taking up 2400 bits. The difference is the extra coding that is applied by the FEC facility at the satellite.

The "Error Count" displayed on the "Real Time" data represents the number of bit errors detected and corrected by the software when decoding each frame of telemetry.

What sort of antenna will I need to use to receive the data from FC1?

When FC1 is operating in "educational" mode then the telemetry transmitter output power will be approx 300mW In this configuration we expect that it will be possible to receive good data with a

simple omni-directional antenna such as a turnstile. When the spacecraft is operating in "amateur" mode, the telemetry power will be approx 9dB lower and therefore a steerable antenna with approx 10dB gain will be required for tIm reception. In amateur mode the transponder will also be active. Circular polarisation, and where appropriate, mast head preamps, are recommended. The spacecraft will operate in "safe" mode immediately after launch. In this mode the transmitter sends low power telemetry only.

Is this the "final" version of the FUNcube dashboard?

NO – There are a number of attributes and functionality that are still work in progress. These include:
Links to Orbitron for location determination and spacecraft pass predictions
Links to a support group
Change graph scaling to remove erroneous zero readings
Making the AFC/AutoTune only track BPSK signals – not just the strongest ones
Allow multiple graph displays
Enable "control-C "commands to copy screen texts (this already works for the debug screen)
Create a Doppler curve graphic at the end of a pass from the detected frequency

REVISION DETAILS

Issue	Date	Description
Release 1.0	13 November 2013	Initial Release to support Dashboard version 798.
Release 1.1	14 November 2013	 Updated to v800.1 of the Dashboard. Page 4 – corrected bandwidth of tuning display to be ±48kHz on centre frequency of Dongle. Folder selection in "Settings" – "Files" now allows for the selection of the target folder. FUNcube Dongle now detected on install with Dashboard running. Note cannot capture with the dongle in this case as awaiting update on audio input
		 devices. "Autotune" is enhanced to remove user involvement when starting. Dashboard now installed by default to unique folder which includes version number to avoid conflicts with earlier versions.
Release 1.2	19 November 2013	 Updated to v806 of the Dashboard Included reference to requirement for .NET Framework 4.0 to install the Dashboard. Warehouse Settings are now retained from this release when updating to a future update. Audio settings updated to recognise changes in audio devices whilst Dashboard still running. Updated error messages. Enhancements to audio capture and recording,

Release 1.3	23 rd December 2013	 Updated to v814 of the Dashboard. Fix for "Hanging at startup" problems, these were due to a bug in the port audio library, now worked 				
		 around. Fix for low monitoring audio volume when using a pro+ dongle. Changed dashboard spectrum view to show correct frequency when using FCD (pro or pro+). Monitors FCD frequency, so will update if FCD tuned by other application. 				
Release 1.4	28 th January 2014	 Updated to v820 of the Dashboard No changes to the User Interface. Decoding routines enhanced for better detection and decode of weak signals. 				
Release 1.5	26 th July 2014	 Updated to v847 of the Dashboard. Bias T functionality for the FUNcube Dongles included in the settings tab. Significant enhancements to the tuning, tracking and decoding algorithms. "AutoTune" limits, if set, now persisted across program restarts. 				
Release 1.6	29 th July 2014	Updated to v848 of the Dashboard. Fixed a bug with the autotune limits on restart of the Dashboard. 				